

Tutorial D

This document gives a BNF grammar for **Tutorial D**. It consists of an edited version of material from Chapter 11 (“**Tutorial D**”) of the book *Database Explorations: Essays on The Third Manifesto and related topics*, by C. J. Date and Hugh Darwen (Trafford, 2010). The productions make use of several self-explanatory abbreviations: *op* for operator, *inv* for invocation, *exp* for expression, and so on. They’re shown in alphabetical order. In Chapter 11 of the book, the section headed **RELATIONS AND ARRAYS** specifies some additional elements that are not properly integrated—for example, there is a production for <relation set>, which is not referenced in any other production. These are properly integrated in the grammar given here.

```
<agg op inv>
 ::= <agg op name>
    ( [ <integer exp> , ] <relation exp> [ , <exp> ] )
    | <n-adic count etc>

<agg op name>
 ::= COUNT | SUM | AVG | MAX | MIN
    | AND | OR | XOR | EXACTLY
    | UNION | D_UNION | INTERSECT | XUNION

<application relation var def>
 ::= VAR <relation var name> <private or public>
    <relation type or init value> <key def list>

<argument exp>
 ::= <exp>

<array cardinality>
 ::= COUNT ( <array var ref> )

<array target>
 ::= <array var ref>

<array var def>
 ::= VAR <array var name> ARRAY <tuple type spec>

<array var ref>
 ::= <array var name>

<assign>
 ::= <scalar assign>
    | <nonscalar assign>

<assignment>
 ::= <assign commalist> <attribute>

<attribute>
 ::= <attribute name> <type spec>

<attribute extractor inv>
 ::= <attribute ref> FROM <tuple exp>

<attribute ref>
 ::= <attribute name>
```

2 *Tutorial D Grammar*

```
<attribute target>
  ::= <attribute ref>
     | <attribute THE_ pv ref>

<attribute THE_ pv ref>
  ::= <THE_ pv name> ( <attribute target> )

<begin transaction>
  ::= BEGIN TRANSACTION

<built in relation op inv>
  ::= <relation selector inv>
     | <THE_ op inv>
     | <attribute extractor inv>
     | <project>
     | <n-adic other built in relation op inv>
     | <monadic or dyadic other built in relation op inv>

<built in scalar op inv>
  ::= <scalar selector inv>
     | <THE_ op inv>
     | <attribute extractor inv>
     | <agg op inv>
     | ... plus the usual possibilities

<built in scalar type name>
  ::= INTEGER | RATIONAL | CHARACTER | BOOLEAN

<built in tuple op inv>
  ::= <tuple selector inv>
     | <THE_ op inv>
     | <attribute extractor inv>
     | <tuple extractor inv>
     | <tuple project>
     | <n-adic other built in tuple op inv>
     | <monadic or dyadic other built in tuple op inv>

<call>
  ::= CALL <user op inv>

<case>
  ::= CASE ; <when spec list> [ ELSE <statement> ]
     END CASE

<commit>
  ::= COMMIT

<compound statement body>
  ::= BEGIN ; <statement list> END

<constraint def>
  ::= CONSTRAINT <constraint name> <bool exp>
```

```

<constraint drop>
    ::= DROP CONSTRAINT <constraint name>

<database relation var def>
    ::= <real relation var def>
       | <virtual relation var def>

<direction>
    ::= ASC | DESC

<divide>
    ::= <relation exp> DIVIDEBY <relation exp> <per>

<do>
    ::= [ <statement name> : ]
       DO <scalar var ref> := <integer exp> TO <integer exp> ;
       <statement>
       END DO

<dyadic compose>
    ::= <relation exp> COMPOSE <relation exp>

<dyadic disjoint union>
    ::= <relation exp> D_UNION <relation exp>

<dyadic intersect>
    ::= <relation exp> INTERSECT <relation exp>

<dyadic join>
    ::= <relation exp> JOIN <relation exp>

<dyadic other built in relation op inv>
    ::= <dyadic union> | <dyadic disjoint union>
       | <dyadic intersect> | <minus> | <included minus>
       | <dyadic join> | <dyadic times> | <dyadic xunion>
       | <dyadic compose> | <matching> | <not matching> | <divide>
       | <summarize>

<dyadic other built in tuple op inv>
    ::= <dyadic tuple union> | <dyadic tuple compose>

<dyadic times>
    ::= <relation exp> TIMES <relation exp>

<dyadic tuple compose>
    ::= <tuple exp> COMPOSE <tuple exp>

<dyadic tuple union>
    ::= <tuple exp> UNION <tuple exp>

<dyadic union>
    ::= <relation exp> UNION <relation exp>

<dyadic xunion>
    ::= <relation exp> XUNION <relation exp>

```

4 *Tutorial D Grammar*

```
<exp>
 ::= <scalar exp>
    | <nonscalar exp>

<extend>
 ::= EXTEND <relation exp> : { <attribute assign commalist> }

<group>
 ::= <relation exp> GROUP ( <grouping> )

<grouping>
 ::= { [ ALL BUT ] <attribute ref commalist> }
      AS <introduced name>

<heading>
 ::= { <attribute commalist> }

<if>
 ::= IF <bool exp> THEN <statement> [ ELSE <statement> ]
      END IF

<included minus>
 ::= <relation exp> I_MINUS <relation exp>

<key def>
 ::= KEY { [ ALL BUT ] <attribute ref commalist> }

<leave>
 ::= LEAVE <statement name>

<matching>
 ::= <relation exp> MATCHING <relation exp>

<minus>
 ::= <relation exp> MINUS <relation exp>

<monadic or dyadic other built in relation op inv>
 ::= <monadic other built in relation op inv>
    | <dyadic other built in relation op inv>

<monadic or dyadic other built in tuple op inv>
 ::= <monadic other built in tuple op inv>
    | <dyadic other built in tuple op inv>

<monadic other built in relation op inv>
 ::= <rename> | <where> | <extend> | <wrap> | <unwrap>
    | <group> | <ungroup> | <tclose>

<monadic other built in tuple op inv>
 ::= <tuple rename> | <tuple extend>
    | <tuple wrap> | <tuple unwrap>

<n-adic compose>
 ::= COMPOSE { <relation exp commalist> }
```

```

<n-adic count etc>
  ::= <agg op name> { <exp commalist> }

<n-adic disjoint union>
  ::= D_UNION [ <heading> ] { <relation exp commalist> }

<n-adic intersect>
  ::= INTERSECT [ <heading> ] { <relation exp commalist> }

<n-adic join>
  ::= JOIN { <relation exp commalist> }

<n-adic other built in relation op inv>
  ::= <n-adic union> | <n-adic disjoint union>
     | <n-adic intersect> | <n-adic join> | <n-adic times>
     | <n-adic xunion> | <n-adic compose>

<n-adic other built in tuple op inv>
  ::= <n-adic tuple union>

<n-adic times>
  ::= TIMES { <relation exp commalist> }

<n-adic tuple union>
  ::= UNION { <tuple exp commalist> }

<n-adic union>
  ::= UNION [ <heading> ] { <relation exp commalist> }

<n-adic xunion>
  ::= XUNION [ <heading> ] { <relation exp commalist> }

<name intro>
  ::= <introduced name> := <exp>

<no op>
  ::= ... zero or more "white space" characters

<nonscalar assign>
  ::= <tuple assign>
     | <relation assign>

<nonscalar exp>
  ::= <tuple exp>
     | <relation exp>

<nonscalar selector inv>
  ::= <tuple selector inv>
     | <relation selector inv>

<nonscalar type spec>
  ::= <tuple type spec>
     | <relation type spec>

```

6 *Tutorial D Grammar*

```
<nonscalar var ref>
 ::= <tuple var ref>
    | <relation var ref>

<nonwith statement body>
 ::= <previously defined statement body commalist>
    | <begin transaction> | <commit> | <rollback>
    | <call> | <return> | <case> | <if> | <do> | <while>
    | <leave> | <no op> | <compound statement body>

<not matching>
 ::= <relation exp> NOT MATCHING <relation exp>

<order item>
 ::= <direction> <attribute ref>

<ordering>
 ::= ORDINAL | ORDERED

<parameter def>
 ::= <parameter name> <type spec>

<per>
 ::= PER ( <relation exp> [ , <relation exp> ] )

<per or by>
 ::= <per>
    | BY { [ ALL BUT ] <attribute ref commalist> }

<possrep component def>
 ::= <possrep component name> <type spec>

<possrep component ref>
 ::= <possrep component name>

<possrep component target>
 ::= <possrep component ref>
    | <possrep THE_ pv ref>

<possrep constraint def>
 ::= CONSTRAINT <bool exp>

<possrep def>
 ::= POSSREP [ <possrep name> ]
           { <possrep component def commalist>
             [ <possrep constraint def> ] }

<possrep THE_ pv ref>
 ::= <THE_ pv name> ( <possrep component target> )
```

```

<previously defined statement body>
 ::= <assignment>
    | <user op def> | <user op drop>
    | <user scalar type def> | <user scalar type drop>
    | <scalar var def> | <tuple var def>
    | <relation var def> | <relation var drop>
    | <constraint def> | <constraint drop>
    | <array var def> | <relation get> | <relation set>

<private or public>
 ::= PRIVATE | PUBLIC

<project>
 ::= <relation exp> { [ ALL BUT ] <attribute ref commalist> }

<real or base>
 ::= REAL | BASE

<real relation var def>
 ::= VAR <relation var name> <real or base>
    <relation type or init value> <key def list>

<relation assign>
 ::= <relation target> := <relation exp>
    | <relation insert>
    | <relation d_insert>
    | <relation delete>
    | <relation i_delete>
    | <relation update>

<relation comp>
 ::= <relation exp> <relation comp op> <relation exp>

<relation comp op>
 ::= = | ≠ | ⊆ | ⊇ | ⊂ | ⊃

<relation d_insert>
 ::= D_INSERT <relation target> <relation exp>

<relation delete>
 ::= DELETE <relation target> <relation exp>
    | DELETE <relation target> [ WHERE <bool exp> ]

<relation exp>
 ::= <relation with exp>
    | <relation nonwith exp>

<relation get>
 ::= LOAD <array target> FROM <relation exp>
    ORDER ( <order item commalist> )

<relation i_delete>
 ::= I_DELETE <relation target> <relation exp>

```

8 *Tutorial D Grammar*

```
<relation insert>
 ::=  INSERT <relation target> <relation exp>

<relation nonwith exp>
 ::=  <relation var ref>
      | <relation op inv>
      | ( <relation exp> )

<relation op inv>
 ::=  <user op inv>
      | <built in relation op inv>

<relation selector inv>
 ::=  RELATION [ <heading> ] { <tuple exp commalist> }
      | TABLE_DEE
      | TABLE_DUM

<relation set>
 ::=  LOAD <relation target> FROM <array var ref>

<relation target>
 ::=  <relation var ref>
      | <relation THE_ pv ref>

<relation THE_ pv ref>
 ::=  <THE_ pv name> ( <scalar target> )

<relation type name>
 ::=  RELATION <heading>

<relation type or init value>
 ::=  <relation type spec> | INIT ( <relation exp> )
      | <relation type spec> INIT ( <relation exp> )

<relation type spec>
 ::=  <relation type name>
      | SAME_TYPE_AS ( <relation exp> )
      | RELATION SAME_HEADING_AS ( <nonscalar exp> )

<relation update>
 ::=  UPDATE <relation target> [ WHERE <bool exp> ] :
      { <attribute assign commalist> }

<relation var def>
 ::=  <database relation var def>
      | <application relation var def>

<relation var drop>
 ::=  DROP VAR <relation var ref>

<relation var ref>
 ::=  <relation var name>

<relation with exp>
 ::=  WITH ( <name intro commalist> ) : <relation exp>
```

```

<rename>
 ::= <relation exp> RENAME { <renaming commalist> }

<renaming>
 ::= <attribute ref> AS <introduced name>
    | PREFIX <character string literal>
      AS <character string literal>
    | SUFFIX <character string literal>
      AS <character string literal>

<return>
 ::= RETURN [ <exp> ]

<rollback>
 ::= ROLLBACK

<scalar assign>
 ::= <scalar target> := <scalar exp>
    | <scalar update>

<scalar comp>
 ::= <scalar exp> <scalar comp op> <scalar exp>

<scalar comp op>
 ::= = | ≠ | < | ≤ | > | ≥

<scalar exp>
 ::= <scalar with exp>
    | <scalar nonwith exp>

<scalar nonwith exp>
 ::= <scalar var ref>
    | <scalar op inv>
    | ( <scalar exp> )

<scalar op inv>
 ::= <user op inv>
    | <built in scalar op inv>

<scalar selector inv>
 ::= <built in scalar literal>
    | <possrep name> ( <argument exp commalist> )

<scalar target>
 ::= <scalar var ref>
    | <scalar THE_ pv ref>

<scalar THE_ pv ref>
 ::= <THE_ pv name> ( <scalar target> )

<scalar type name>
 ::= <user scalar type name>
    | <built in scalar type name>

```

10 *Tutorial D Grammar*

```
<scalar type or init value>
 ::= <scalar type spec> | INIT ( <scalar exp> )
    | <scalar type spec> INIT ( <scalar exp> )

<scalar type spec>
 ::= <scalar type name>
    | SAME_TYPE_AS ( <scalar exp> )

<scalar update>
 ::= UPDATE <scalar target> :
    { <possrep component assign commalist> }

<scalar var def>
 ::= VAR <scalar var name> <scalar type or init value>

<scalar var ref>
 ::= <scalar var name>

<scalar with exp>
 ::= WITH ( <name intro commalist> ) : <scalar exp>

<selector inv>
 ::= <scalar selector inv>
    | <nonscalar selector inv>

<statement>
 ::= <statement body> ;

<statement body>
 ::= <with statement body>
    | <nonwith statement body>

<subscript>
 ::= <integer exp>

<summarize>
 ::= SUMMARIZE <relation exp> [ <per or by> ] :
    { <attribute assign commalist> }

<summary>
 ::= <summary spec> ( [ <integer exp> , ] [ <exp> ] )

<summary spec>
 ::= COUNT | COUNTD | SUM | SUMD | AVG | AVGD | MAX | MIN
    | AND | OR | XOR | EXACTLY | EXACTLYD
    | UNION | D_UNION | INTERSECT | XUNION

<tclose>
 ::= TCLOSE ( <relation exp> )

<THE_ op inv>
 ::= <THE_ op name> ( <scalar exp> )
```

```

<tuple assign>
  ::= <tuple target> := <tuple exp>
     | <tuple update>

<tuple comp>
  ::= <tuple exp> <tuple comp op> <tuple exp>
     | <tuple exp> ∈ <relation exp>
     | <tuple exp> ∉ <relation exp>

<tuple comp op>
  ::= = | ≠

<tuple component>
  ::= <attribute name> <exp>

<tuple exp>
  ::= <tuple with exp>
     | <tuple nonwith exp>

<tuple extend>
  ::= EXTEND <tuple exp> : { <attribute assign commalist> }

<tuple extractor inv>
  ::= TUPLE FROM <relation exp>

<tuple nonwith exp>
  ::= <tuple var ref>
     | <tuple op inv>
     | <array var ref> ( <subscript> )
     | ( <tuple exp> )

<tuple op inv>
  ::= <user op inv>
     | <built in tuple op inv>

<tuple project>
  ::= <tuple exp> { [ ALL BUT ] <attribute ref commalist> }

<tuple rename>
  ::= <tuple exp> RENAME { <renaming commalist> }

<tuple selector inv>
  ::= TUPLE { <tuple component commalist> }

<tuple target>
  ::= <tuple var ref>
     | <tuple THE_ pv ref>

<tuple THE_ pv ref>
  ::= <THE_ pv name> ( <scalar target> )

<tuple type name>
  ::= TUPLE <heading>

```

12 *Tutorial D Grammar*

```
<tuple type or init value>
  ::= <tuple type spec> | INIT ( <tuple exp> )
     | <tuple type spec> INIT ( <tuple exp> )

<tuple type spec>
  ::= <tuple type name>
     | SAME_TYPE_AS ( <tuple exp> )
     | TUPLE SAME_HEADING_AS ( <nonscalar exp> )

<tuple unwrap>
  ::= <tuple exp> UNWRAP ( <unwrapping> )

<tuple update>
  ::= UPDATE <tuple target> :
     { <attribute assign commalist> }

<tuple var def>
  ::= VAR <tuple var name> <tuple type or init value>

<tuple var ref>
  ::= <tuple var name>

<tuple with exp>
  ::= WITH ( <name intro commalist> ) : <tuple exp>

<tuple wrap>
  ::= <tuple exp> WRAP ( <wrapping> )

<type spec>
  ::= <scalar type spec>
     | <nonscalar type spec>

<ungroup>
  ::= <relation exp> UNGROUP ( <ungrouping> )

<ungrouping>
  ::= <attribute ref>

<unwrap>
  ::= <relation exp> UNWRAP ( <unwrapping> )

<unwrapping>
  ::= <attribute ref>

<user op def>
  ::= <user update op def>
     | <user read-only op def>

<user op drop>
  ::= DROP OPERATOR <user op name>

<user op inv>
  ::= <user op name> ( <argument exp commalist> )
```

```

<user read-only op def>
  ::= OPERATOR <user op name> ( <parameter def commalist> )
     RETURNS <type spec> ;
     <statement>
     END OPERATOR

<user scalar root type def>
  ::= TYPE <user scalar type name>
     [ <ordering> ] <possrep def list>
     INIT ( <literal> )

<user scalar type def>
  ::= <user scalar root type def>

<user scalar type drop>
  ::= DROP TYPE <user scalar type name>

<user update op def>
  ::= OPERATOR <user op name> ( <parameter def commalist> )
     UPDATES { [ ALL BUT ] <parameter name commalist> } ;
     <statement>
     END OPERATOR

<var ref>
  ::= <scalar var ref>
     | <nonscalar var ref>

<virtual relation var def>
  ::= VAR <relation var name> VIRTUAL
     ( <relation exp> ) <key def list>

<when spec>
  ::= WHEN <bool exp> THEN <statement>

<where>
  ::= <relation exp> WHERE <bool exp>

<while>
  ::= [ <statement name> : ]
     WHILE <bool exp> ;
     <statement>
     END WHILE

<with statement body>
  ::= WITH ( <name intro commalist> ) : <statement body>

<wrap>
  ::= <relation exp> WRAP ( <wrapping> )

<wrapping>
  ::= { [ ALL BUT ] <attribute ref commalist> }
     AS <introduced name>

```